

FENCE & BARN RED

OIL-BASED FENCE & BARN PAINT

Direct from the
Heart of Horse
Country!

DESCRIPTION

Premium oil-based fence & barn paint.

FEATURES

- Linseed-oil/alkyd formulation for durability and flexibility.
- Self-priming on new lumber.
- Excellent weather protection.
- Excellent hiding power.
- Excellent color retention.
- Safe around valuable horses and livestock – lead-free.
- Oil-based formulation is resistant to rust.
- Cleanup with mineral spirits.

RECOMMENDED USES

- Plank fences
- Barns
- Barn stalls
- Barn interiors
- Silos
- Farm buildings
- New and weathered wood
- Concrete, masonry, and brick
- Metal structures
- Gates
- Loading areas and chutes
- Not for use on new or uncoated galvanized steel
- Not suitable for flooring or high abrasion surfaces

CHARACTERISTICS

Color	Red
Finish	Semi-Gloss
Flash point	105°F (PMCC)
Viscosity	90 KU
Available Packaging	5-gal pails, 55-gal drums
VOC	Less than 380 grams/liter

SHELF LIFE

2 years in unopened cans. To maximize shelf life, store out of direct sunlight. Product will not be affected if stored below 32°F.

Settling can occur, product must be shaken vigorously before use. For best results, flip pails upside down while shaking.

COVERAGE

3 & 4 board fence	16 ft. / gal., both sides
1 board fence	26 ft. / gal., both sides
Barns	250 sq. ft. / gal.

Typical fence posts are placed 8 feet apart.

Coverage depends on many factors such as porosity and roughness of the substrate and material losses during application. Using less than recommended material will lead to decreased durability. May require two coats for best results on previously unpainted surfaces.

DRYING TIME @ 77°F / RH 50%

Set to touch	4-6 hours
Re-coat	8 hours
Fully dry	24 hours
Drying times vary based on rain, dew, and temperature.	
Do not paint if rain is expected within 8 hrs.	

RECOMMENDED FILM THICKNESS

Wet film – per coat	3.5 to 6.0 mils
Dry film – per coat	1.5 to 2.5 mils

APPLICATION

Product should be thoroughly mixed before use. No thinning needed – if necessary, thin with 4 fl. oz. mineral spirits per gal. paint.

Application temp.	above 40°F
Method	Brush, roll, or spray

Allow new wood 1 to 3 months to weather to reduce moisture content (less than 15% recommended).

Do not paint the underside of fence planks.

Airless spray:

Rating	0.5 gal / minute minimum
Pressure	1800-2500psi
Filter	30 to 60 mesh
Tip Size	0.017" to 0.025"

SURFACE PREPARATION

For greatest durability make sure surface is scraped, sanding, or pressure washed thoroughly by removing any peeling or flaking paint before applying. For metal surfaces, ensure surface is clean.