

Product Description

A high gloss industrial maintenance enamel formulated for exterior or interior protection of steel, aluminum and wood. This product provides excellent protection and decoration of metal exposed to heavy abrasion, including scrubbing with industrial cleanser or scouring agents. Also offers excellent resistance to water, oil, grease and mild industrial fumes. Applications include metal buildings, tanks, machinery, walls, metal fencing, structural steel and barn interiors.

Coverage

Up to 325 square feet per gallon on smooth surfaces. Coverage will be less on rusted, rough, and/or weathered surfaces and may require two coats for best results.

Dry Time

Dries to touch in 4 - 6 hours under normal environmental conditions. Allow to dry 12 hours before recoating.

Surface Preparation

The surface must be clean, free of dirt, chalk, mildew, oil and other foreign matter. Remove by washing with a stiff brush using a non-residue all-purpose cleaner and water. Rinse thoroughly. Pressure washing is the best overall cleaning method if available. If the surface is badly peeling and weathered, scrap and clean down to a sound substrate. On rusted metal surface use a rust inhibitive primer after cleaning. On new metal surfaces remove factory oils by wiping with thinner soaked rags. For best results, prime iron and steel with a rust inhibitive primer. Non rusted galvanized and aluminum surfaces should be primed with galvanized and aluminum primer to insure maximum adhesion. On wood surfaces, this product is self priming.

Application

Stir thoroughly before applying. Only paint when the air and surface temperatures are above 40°F (5°C). Do not paint in extremely damp weather or when rain is threatening. Apply with a brush, roller or spray. No thinning is recommended. For spray application use a .015" to .021" tip. Clean tools and equipment with mineral spirits.



ENAMEL COAT

HIGH - GLOSS INDUSTRIAL MAINTENANCE COATING

- **Resists Rust**
- **High Gloss**
- **Abrasion Resistant**

WHITE

- **Metal Buildings / Tanks**
- **Wood / Concrete**
- **Trim**

5 U.S. Gal.

18.9 L

 Lexington
Paint & Supply, INC.

103 PARK CENTRAL COURT • NICHOLASVILLE, KY • (859) 885-7276 • www.lexpaint.com

CAUTION! COMBUSTIBLE! See Other Cautions on Side Panel

Storage & Disposal

Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

CAUTION! COMBUSTIBLE

Contains Petroleum

Distillate

Keep away from heat, spark and flame. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

USE WITH ADEQUATE VENTILATION

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN

Cas No.	Common Name
64742-47-8	Mineral Spirits
1317-65-3	Calcium Carbonate
13701-59-2	Barium Metaborate
13463-67-7	Titanium Dioxide
66070-60-8	Alkyd Resin

MAX VOC Content 450 grams/liter