

Product Description

A 100% acrylic direct to metal semi-gloss enamel with outstanding corrosion resistance and durability. This product offers excellent performance on metal buildings, tanks, metal roofs and structural steel as well as wood and concrete surfaces. Can also be used in interior applications and light to moderate industrial environments including galvanized metal and aluminum. Fast dry time and soap and water clean up maximize production.

Coverage

Up to 350 square feet per gallon (4 mils wet) on smooth surfaces. Coverage will be less on rusted, rough and/or weathered surfaces and may require two coats for best results.

Dry Time

Dries to touch in 30 minutes and can be recoated in 4 hours under normal environmental conditions.

Surface Preparation

The surface must be clean, free of dirt, chalk, mildew, oil and other foreign matter. Remove by washing with a stiff brush using a non-residue all-purpose cleaner and water (do not use hydrocarbon solvents). Rinse thoroughly. Remove loose or peeling paint and rust with a wire brush and scraper. Pressure washing is the best overall method if available. If surface is badly peeling and weathered, clean surfaces down to a sound substrate. On rusty metal clean first and always apply a rust inhibitive primer. On new galvanized and aluminum surfaces this product is self priming. On new wood use an appropriate stain killing primer to avoid tannin staining.

Application

Stir thoroughly before applying. Only paint when the air and surface temperatures are above 50°F (10°C). Do not paint in extremely damp weather or when rain is threatening. Apply with brush, roller or spray. For spray application use a .015" to .019" tip. In the early stages of drying this product is sensitive to rain, dew, high humidity and moisture condensation. Avoid these conditions during the first 4 hours after application. When applying this product always intermix (box) containers together to insure color uniformity. Product can be thinned with water if necessary. Clean brushes, rollers, tools and hands with warm soapy water.

ENAMEL PRO

100 % ACRYLIC SEMI-GLOSS DIRECT TO METAL ENAMEL

- **Resists Rust**
- **Excellent Durability**
- **Soap & Water Clean Up**

WHITE

- **Metal Buildings / Tanks**
- **Metal Roofs / Aluminum**
- **Wood / Concrete**

5 U.S. Gal.

 Lexington
Paint & Supply, INC.

18.9 L

6 49928 25105 9

Storage & Disposal

Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations. DO NOT FREEZE.

CAUTION!

May cause eye and skin irritation. Avoid breathing vapors or spray mist. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits wear an appropriate respirator (NIOSH approved) during and after application. Follow respirator use.

AVOID CONTACT WITH EYES AND SKIN.

Wash thoroughly after use. Close container after each use.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists get medical attention.

IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues get medical attention.

IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.

DO NOT TAKE INTERNALLY.

Cas No.	Common Name
7732-18-5	Water
Unknown	Acrylic Polymer
13463-67-7	Titanium Dioxide
13701-59-2	Barium Metaborate
66402-68-4	Calcined Clay
1317-65-3	Calcium Carbonate

MAX VOC Content 100 grams/liter