

## Product Description

A highly economical black acrylic lacquer formulated specifically for wood plank fences in the equine industry. This product dries to an extremely tough and durable semi-gloss finish that will not chalk, peel or rub off. Can be applied over virtually any type of marginally prepared, painted or unpainted, surface with excellent results. This product is lead-free and safe around valuable livestock. Also makes an economical coating for barns, sheds, silos and metal or concrete buildings. It is not recommended for interior applications.

## Coverage

BARNs - 200 to 300 square feet per gallon on smooth surfaces.

FENCEs - 16 running feet of 3 or 4 board fence (1 panel both sides) per gallon.

New, extremely rough cut and/or weathered surfaces will take more product and may require two coats for best results. Less than recommended coverage rates will see a reduction in durability.

## Dry Time

Product dries overnight by solvent evaporation only but may remain slightly tacky for several days depending on surface painted and amount of material applied. On metal or non-porous surfaces dry time may be longer.

## Application

Mix paint thoroughly before application. No thinning is recommended. Make sure fence or barn to be painted is free of mud, dirt and loose or peeling paint. Use scrapers and wire brushes to remove as much as possible. In severe cases pressure washing is recommended. Allow new lumber to weather 1-2 months to reduce the moisture content. This product can be applied with brushes, rollers or spray at any temperature (even below freezing) with excellent results. Always avoid breathing vapor and spray mist and use protective clothing and eye protection.

## Spray Equipment

- \* Minimum recommended pump rating -2/3 gallons per minute. (Graco GM-3000/GMax 3900 or equivalent)
- \* Filter - 10 mesh suction strainer, 30 mesh pump filter
- \* Tip - .019" to .023" with a 6" pattern for wood plank fence or a 10" to 12" pattern for barns. Reversible type tip recommended.
- \* Clean up with lacquer thinner.
  - Fence - Graco # 286-321 / 286-323 or equivalent
  - Barns - Graco # 286-621 / 286-623 or equivalent

# FENCE COAT

## ACRYLIC LACQUER

- *Exceptional Durability*
- *Highly Economical*
- *Safe Around Livestock*

**BLACK**

5 U.S. Gal.



**Lexington**  
**Paint & Supply, INC.**

18.9 L

103 PARK CENTRAL COURT • NICHOLASVILLE, KY • (859) 885-7276 • [www.lexpaint.com](http://www.lexpaint.com)

## Storage & Disposal

Product does not freeze and can be stored outside or in unheated areas. Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations. Do not transfer contents to other containers for storage or disposal.

**Contains not less than 40 percent by volume post consumer coating.**

## WARNING!

**FLAMMABLE  
VAPOR HARMFUL**

Contains Petroleum  
Distillate, Xylene

Keep away from heat, spark and flame. Use only in well ventilated areas. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear a properly fitted respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with eyes and skin by wearing protective clothing and eye protection.

**USE WITH ADEQUATE VENTILATION**  
**Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN**

**MAX VOC Content 680 grams/liter**



**WARNING! Vapor Harmful! Flammable Liquid & Vapor.**

See Other Cautions  
on Side Panel