

Product Description

A 100% acrylic paint formulated especially for wood plank fences. This product offers exceptional economy and durability in a user friendly water based formulation. Provides excellent weather protection and decoration, and is safe around valuable livestock. Can be applied directly to new, weathered or previously painted lumber with the convenience of soap and water clean up. Other applications include barns, sheds and other farm structures. Not suitable for flooring or other high traffic areas

Coverage

BARNs - 300 to 350 square feet per gallon on smooth surfaces.

FENCEs - 16 running feet of 3 or 4 rail fence (both sides) per gallon.

Coverage will be less on rough cut lumber, textured and/or porous surfaces and may require two coats for best results.

Dry Time

Dries to touch in one hour. Can be recoated in four hours. May be slightly sticky upon cure.

Thinning & Clean Up

If necessary thin with small amounts of water. Clean brushes, rollers, spray equipment and hands with warm soapy water.

Application

Clean surface thoroughly. Remove dust, dirt or oil by washing the surface with a non-residue all-purpose cleaner. Remove loose or peeling paint and rust with a wire brush and scraper. Pressure washing is the best overall method if available. Caulk cracks and crevices around windows, doors and trim. For unpainted surfaces two coats are recommended. On rusty metal areas spot prime with a rust inhibitive primer. Stir paint thoroughly before applying. Only paint when the air and surface temperatures are above 50°F (10°C). Do not paint in extremely damp weather or when rain is threatening. For spray application use a .017" to .021" tip.



FENCE PRO

100% ACRYLIC LATEX FENCE & BARN PAINT

- Self Priming
- Non-Toxic
- Soap & Water Cleanup

BLACK

- Barns / Fences
- New / Weathered Wood
- Concrete / Metal

5 U.S. Gal.

 **Lexington**
Paint & Supply, INC.

18.9 L

Storage & Disposal

Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations. DO NOT FREEZE.

CAUTION!

May cause eye and skin irritation. Avoid breathing vapors or spray mist. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits wear an appropriate respirator (NIOSH approved) during and after application. Follow respirator use. AVOID CONTACT WITH EYES AND SKIN. Wash thoroughly after use. Close container after each use.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.**

IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues **get medical attention.**

IF SWALLOWED: Drink 2 glasses of water.

Get medical attention immediately.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

Cas No.	Common Name
7732-18-5	Water
Unknown	Acrylic Polymer
1333-86-4	Carbon Black
1317-65-3	Calcium Carbonate

MAX VOC Content 100 grams/liter