

## Product Description

Shopcoat Primer is a low cost, fast drying, rust inhibitive primer. Offers good corrosion resistance, excellent hiding, and a lead-free formulation. Can be top coated with all conventional alkyds and latex finishes.

## Application

- \* Recommended spread rate - 375 sq. ft. per gal.
- \* Surface preparation - Surface must be clean and dry. Remove all oil, dust, dirt, loose rust, peeling paint or other contaminants before applying.
- \* Method - brush, roll, spray.
- \* Application temperature- Above 45° F.
- \* Mix well before applying.
- \* Dry to touch in 30 minutes. Recoat in 2 hours.
- \* Clean up with mineral spirits.
- \* Contains less than 450 grams per liter VOC.
- \* No thinning recommended.



6 49928 67105 5

## Spray Equipment

- \* Rating - 0.5 gal per min
- \* Pressure - 2500 psi
- \* Tip - 0.017" - 0.021"
- \* Filter - none

## CAUTION!

### COMBUSTIBLE

Contains Petroleum Distillate

Keep away from heat, spark and flame. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

### USE WITH ADEQUATE VENTILATION

**Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN**

# SHOPCOAT PRIMER

## 299 WHITE

5 U.S. Gallons (18.925 LITERS)

### CAUTION! COMBUSTIBLE

See Other Cautions on Side Panel



**Lexington  
Paint & Supply, INC.**

103 PARK CENTRAL COURT, NICHOLASVILLE, KY  
(859) 885-7276