

DRIVEWAY SEALER

ACRYLIC LACQUER DRIVEWAY SEALER

DESCRIPTION

Highly economical black acrylic lacquer formulated specifically for driveways.

FEATURES

- Product dries to an extremely tough and durable finish that will not chalk, peel, or rub off.
- Excellent weather protection.
- Can be applied over virtually any type of marginally prepared driveway.
- Can be applied over previously painted or unpainted surfaces.
- Can be applied in any temperature.
- Will provide superior longevity when compared to emulsion products.
- Lead-free and safe for all types of asphalt.
- 3 to 5 years of durability.
- Not recommended for interior applications.
- Clean up with lacquer thinner.

RECOMMENDED USES

- Asphalt driveways

CHARACTERISTICS

Color	Black
Finish	Semi-gloss
Flash point	88°F (PMCC)
Viscosity	72 KU
Available Packaging	5-gal pails, 55-gal drums

SHELF LIFE

2 years in unopened cans. To maximize shelf life, store out of direct sunlight. Product will not be affected if stored below 32°F.

Settling can occur, product must be shaken vigorously before use. For best results, flip pails upside down while shaking.

COVERAGE

Driveways 125 sq. ft. / gal.

Coverage depends on many factors such as porosity and roughness of the substrate and material losses during application. Using less material than recommended will see a decrease in durability.

DRYING TIME @ 77°F / RH 50%

Set to touch	6 hours
Drive On	24 hours

Drying times are affected by exposure to sunlight, rain, dew, and temperature. Do not paint if rain is expected within 8 hours.

RECOMMENDED FILM THICKNESS

Wet film – per coat	6.0 to 10.0 mils
Dry film – per coat	2.0 to 4.0 mils

APPLICATION

Product should be thoroughly mixed before use. Thinning not recommended.

Application temp.	Any
Method	Brush, roll, or spray

Airless spray:	
Rating	0.5 gal. / min. minimum
Pressure	1800–2500 psi
Filter	10 mesh suction strainer, 30 mesh pump filter recommended
Tip Size	0.017" to 0.021"

Sprayer must be rated for spraying lacquer. Call us for help determining if your sprayer is capable of spraying this product.

Roller application: use thick nap roller.

Clean up with lacquer thinner.

SURFACE PREPARATION

For greatest durability make sure surface is free of dirt, debris, and water.