

Product Description

A premium quality oil-based paint formulated especially for fences and barns. It is easy to apply and offers long term durability on new or weathered surfaces. This product contains an effective mildewcide which is designed to resist the growth of mildew on the dried paint film. Can also be used on interior barn surfaces, silos, sheds, concrete or properly prepared metal.

Coverage

BARNs - 300 to 350 square feet per gallon on smooth surfaces.

FENCEs - 16 running feet of 3 or 4 rail fence (both sides) per gallon.

Coverage will be less on rough cut lumber, textured and/or porous surfaces and may require two coats for best results. No thinning recommended.

Important Facts About Mildew

Where high temperature and humidity are common, mildew can be a problem. Mildew is a fungus that looks like dirt, but detergent will not remove it. If you see mildew, or if you do not see any but know it is a problem in your area, scrub the surface before painting with a commercial mildew remover or 1 part liquid chlorine bleach to 3 parts water. Wear protective clothing and avoid skin or eye contact when working with bleach solution. Rinse the surface thoroughly.

Dry Time

Dries to touch in 4 - 6 hours under normal environmental conditions. Can be recoated after overnight dry.

Application

Clean surface thoroughly. Remove dust, dirt or oil by washing the surface with a non-residue all-purpose cleaner. Remove loose or peeling paint and rust with a wire brush and scraper. Pressure washing is the best overall method if available. Caulk cracks and crevices around windows, doors and trim. For unpainted surfaces two coats are recommended. On rusty metal areas spot prime with a rust inhibitive primer. Stir paint thoroughly before applying. Only paint when the air and surface temperatures are above 45°F (8°C). Do not paint in extremely damp weather or when rain is threatening. For spray application use a .017" to .021" tip. Clean tools and equipment with mineral spirits.

- Self Priming
- Mildew Resistant
- Safe Around Livestock

WHITE

- Wood Fences / Barns
- Concrete / Masonry
- Metal

5 U.S. Gal.

 **Lexington**
Paint & Supply, INC.

18.9 L

103 PARK CENTRAL COURT • NICHOLASVILLE, KY • (859) 885-7276 • www.lexpaint.com

CAUTION! COMBUSTIBLE! See Other Cautions on Side Panel

Storage & Disposal

Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

CAUTION! COMBUSTIBLE

Contains Petroleum
Distillate

Keep away from heat, spark and flame. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

USE WITH ADEQUATE VENTILATION
Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN

Cas No.	Common Name
1317-65-3	Calcium Carbonate
64742-47-8	Mineral Spirits
67745-08-1	Bodied Linseed Oil
13463-67-7	Titanium Dioxide
1897-45-6	Clorothalonil
66070-60-8	Alkyd Resin

MAX VOC Content 380 grams/liter

