

Product Description

A bright, reflective, heavy duty aluminum paint. It is a perfect product for areas that require heat reflection. It is non-toxic when dry and can be used for exterior or interior application on wood or metal. Typical areas of usage includes grain bins, tanks, roofing, chain-link fencing, piping, machinery and equipment.

Coverage

Up to 400 square feet per gallon on smooth sealed surfaces. Coverage will be less on rough, textured and/or porous surfaces and may require two coats for best results.

Surface Preparation

Remove all traces of loose peeling paint, rust, oil, dirt and other foreign matter from the surface to be painted. Rusted areas must be scrapped, wire brushed or blasted clean. Pressure washing is the best overall cleaning method if available. Blasted metal surfaces should be coated with a rust inhibitive primer before applying this product.

RUSTED METAL SURFACES:

Follow proper surface preparation methods. Spot prime rusted areas with a rust inhibitive primer.

NEW METAL SURFACES:

Remove any flash rust. Remove factory oils by wiping with thinner soaked rags. Ferrous metals should be primed with a rust inhibiting primer. New galvanized metal should be primed with a galvanized metal primer.

WOOD SURFACES:

Product is self priming. On bare or weathered wood, two coats are required for best results.

Application

Stir thoroughly with a circular lifting motion. To assure proper uniformity and color, pour contents from one container to another, box together. Stir occasionally during use. Apply at temperatures between 50° - 90°F. Avoid damp weather. Product may be applied by brush, roller or spray. Thinning is not recommended. Apply thin (1-4 mils wet) even coats. Heavy coats will make this paint run and will retard drying. Dries to touch in 4-6 hours under normal humidity and temperature. Allow a minimum of 24 hours between coats. For spray application, use a .017 to .021 tip. Clean tools and equipment with mineral spirits.

LIQUID ALUMINUM

OIL-BASED ALUMINUM PAINT

- *Bright Finish*
- *Heat Reflective*
- *Non Toxic When Dry*
- *Roofs / Tanks*
- *Grain Bins / Silos*
- *Metal or Wood*

5 U.S. Gal.

 Lexington
Paint & Supply, INC.

18.9 L

103 PARK CENTRAL COURT • NICHOLASVILLE, KY • (859) 885-7276 • www.lexpaint.com

Storage & Disposal

Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

CAUTION!
COMBUSTIBLE
Contains Petroleum
Distillate

Keep away from heat, spark and flame. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

USE WITH ADEQUATE VENTILATION

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN

Cas No.	Common Name
64742-47-8	Mineral Spirits
67746-08-1	Bodied Linseed Oil
Unknown	Petroleum Resin
7429-90-5	Aluminum Paste
64742-95-6	Aromatic Solvent

MAX VOC Content 500 grams/liter



CAUTION! COMBUSTIBLE! See Other Cautions on Side Panel