

Product Description

Black Asphalt is a very heavily bodied oil designed for application on wood fences, barns and barn roofs. When properly applied this product gives 1 to 3 years waterproofing/sealing. Black Asphalt initially goes on with a high gloss, but quickly flattens to a brownish black color. This product is also popular on barns, run in sheds, barn roofs and tanks.

Coverage

FENCE - 3 & 4 board fence - 1.4 to 1.7 gal. per panel (16 ft.). 1 board fence - .9 gal. per panel (16 ft.). Less than recommended application will see a marked difference in durability.

Application

Apply to clean dry surface with brush, roller, or spray. For spray applications the product must be heated to approximately 100°F before being applied to reduce viscosity.

Surface preparation - Flaking, blistering and peeling paint must first be removed.

Apply at full body. Clean up with mineral spirits. Contains less than 500 grams per liter VOC.

WARNING - Product is combustible and will burn. Use only safe and UL listed heating equipment.

CAUTION - Material will ignite upon contact with ignition source.

DO NOT PRINT
FOR ONLINE
REFERENCE ONLY

BLACK ASPHALT

ASPHALT FENCE COATING

- *Barns / Fences*
- *Metal*
- *Concrete/Masonry*
- *Safe Around Livestock*
- *One Coat*
- *Economical*

5 U.S. Gal.

 **Lexington**
Paint & Supply, INC.

18.9 L

103 PARK CENTRAL COURT • NICHOLASVILLE, KY • (859) 885-7276 • www.lexpaint.com

CAUTION! COMBUSTIBLE! See Other Cautions on Side Panel

Spray Equipment

Rating - 1.0 gal per min or greater.
Pressure - maximum 3000 psi
Filter - none
Tip - 0.025" - 0.031"

CAUTION! COMBUSTIBLE

Contains Petroleum
Distillate

Keep away from heat, spark and flame. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

USE WITH ADEQUATE VENTILATION

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF
CHILDREN**



6 49928 13055 2