

## Product Description

A premium grade asphalt based aluminum roof coating formulated for all types of roofs. Ideally suited for metal roofs. Helps stop and prevent rust while keeping the building cooler in summer months. Helps preserve built up composition and shingled asphalt roofs by reflecting damaging sunlight. This product is self priming and can be spray applied directly to rusted metal surfaces with excellent results. Also used on metal buildings, tanks, grain bins and silos.

## Coverage

Up to 350 square feet per gallon on smooth sealed surfaces. Coverage will be less on rusted, rough and weathered surfaces or roofing.

## Surface Preparation

Remove all loose dirt, slag and foreign matter from the roof surface. Rusted areas should be wire brushed clean. Repair all broken or rotted spots and tighten down all loose screws in sheet metal roofing. Cracks, crevices and holes should be patched with a fibered roof cement first. Not recommended over flood coats of asphalt or recently hot-mopped roofs until the roof has cured for at least one year. On rusted metal surfaces a metal primer will extend the life of this coating and retard corrosion.

## Application

Stir thoroughly with a circular lifting motion before and occasionally during application to assure proper uniformity and color. Apply liberally with a roof brush, long-napped roller or spray gun. For a spray application a .017" to .021" tip is recommended. When brushing, apply in only one direction and avoid overlapping. Over brushing will interfere with the leafing properties of the aluminum. No thinning is recommended. Always apply to a dry surface. Application to a damp surface will cause this product to appear brown. Clean tools with mineral spirits. Dry time is approximately 2 hours.

# ASPHALT ALUMINUM REFERENCE ONLY PREMIUM

## ROOF COATING

- *Heat Reflective*
- *Metal Roofs / Tanks*
- *Helps Stop and Prevent Rust*
- *Grain Bins / Silos*
- *Reduces Energy Costs*
- *Factories / Built Up Roofs*

5 U.S. Gal.

 **Lexington**  
**Paint & Supply, INC.**

18.9 L

103 PARK CENTRAL COURT • NICHOLASVILLE, KY • (859) 885-7276 • [www.lexpaint.com](http://www.lexpaint.com)

## Storage & Disposal

Keep container closed when not in use. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**CAUTION!**  
**COMBUSTIBLE**  
Contains Petroleum  
Distillate

Keep away from heat, spark and flame. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

**USE WITH ADEQUATE VENTILATION**  
**Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**DO NOT TAKE INTERNALLY.**  
**KEEP OUT OF REACH OF CHILDREN**

Manufactured to meet ASTM D-2824, Type I

Cas No.	Common Name
64742-47-8	Mineral Spirits
8052-42-4	Asphalt
Unknown	Petroleum Resin
7429-90-5	Aluminum Paste
64742-95-6	Aromatic Solvent

**MAX VOC Content 500 grams/liter**



**CAUTION! COMBUSTIBLE!** See Other Cautions on Side Panel